
TECHNICAL DATA

USE AND APPLICATION

1120 is a paraffin solvent containing carbon-bisulfide. It has a proven history of wide spread success in dissolving both paraffin and asphaltenes.

1120 can be used as it is shipped or it can be diluted. Typically 1120 is diluted with xylene or toluene, but a heavy aromatic can be used.

Contact Lindon for more information on testing paraffin solvents and on using 1120 as a base material for formulating.

TYPICAL PROPERTIES

Flash Point-20°F
Specific Gravity 1.055-1.075

Insoluble in Water

Soluble in Xylene

Soluble in Heavy Aromatic Solvent

Appearance Slightly hazy to clear amber liquid
pH (in 5% IPA).....7.7-8.7

STORAGE AND HANDLING

For Industrial Use Only. Avoid prolonged or repeated contact with skin, eyes and clothing. Do **NOT** ingest. In case of contact with eyes flush with water for at least 15 minutes and get immediate medical attention. Refer to the MSDS for complete handling instructions. **Store away from open flame. Avoid strong oxidizers.**

DISCLAIMER OF LIABILITY

The information in this bulletin is believed to be accurate, however all recommendations are made without warranty, since the conditions of use are beyond LINDON'S control. The listed properties are illustrations only, and not product specifications. LINDON disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its' products in combination with any other material or in any process.