

---

## TECHNICAL DATA

---

### USE AND APPLICATION

1660 is a concentrated blend of a neutralized sulfonate and a polyol, chosen to specifically work well in this formula. It is concentrated and should be used as a base to formulate finished products.

1660 is designed for use in paraffinic systems. It is specifically used for tank treating or bad oil treatment. 1660 is also useful as a base for paraffin dispersants.

---

### TYPICAL PROPERTIES

Flash Point .....	63°F
Pour Point.....	<-22°F
Specific Gravity .....	0.954-0.996
Insoluble in Water	
Soluble in Xylene	
Soluble in Heavy Aromatic Solvent	
Appearance .....	Dark Amber liquid
RSN .....	13.8

---

### STORAGE AND HANDLING

**For Industrial Use Only.** Avoid prolonged or repeated contact with skin, eyes and clothing. Do **NOT** ingest. In case of contact with eyes flush with water for at least 15 minutes and get immediate medical attention. Refer to the MSDS for complete handling instructions. **Store away from open flame. Avoid strong oxidizers.**

### DISCLAIMER OF LIABILITY

The information in this bulletin is believed to be accurate, however all recommendations are made without warranty, since the conditions of use are beyond LINDON'S control. The listed properties are illustrations only, and not product specifications. LINDON disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its' products in combination with any other material or in any process.