
TECHNICAL DATA

USE AND APPLICATION

6662 is a concentrated H₂S scavenger. It should be diluted in a blend of water and isopropyl alcohol. One drum of 6662 will make two or three drums of finished product.

6662 should be injected directly into the gas flow or added down hole to remove H₂S gas. The resulting products are not hazardous and will provide some corrosion protection.

Contact Lindon for more information of treating and removing H₂S.

TYPICAL PROPERTIES

Flash Point	120°F
Specific Gravity	1.055-1.085
Soluble in Water	
Soluble in Isopropanol	
Appearance	Clear to amber liquid, mild odor
pH	10.8-11.9

STORAGE AND HANDLING

For Industrial Use Only. Avoid prolonged or repeated contact with skin, eyes and clothing. Do **NOT** ingest. In case of contact with eyes flush with water for at least 15 minutes and get immediate medical attention. Refer to the MSDS for complete handling instructions. **Store away from open flame. Avoid strong oxidizers.**

DISCLAIMER OF LIABILITY

The information in this bulletin is believed to be accurate, however all recommendations are made without warranty, since the conditions of use are beyond LINDON'S control. The listed properties are illustrations only, and not product specifications. LINDON disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its' products in combination with any other material or in any process.