

MATERIAL SAFETY DATA SHEET
LINDON MANUFACTURING AND LABORATORY
7614 WALLISVILLE, HOUSTON, TX 77020
PHONE (713) 672-4450 FAX (713) 675-2206

PRODUCT NAME: 6682

CHEMTREC EMERGENCY: 1-800-424-9300 U.S. OR CANADA 1-703-527-3887

HAZARD RATING		MANUFACTURER	
N4 - EXTREME	FIRE 3		
F3 - HIGH	HEALTH 2		
P2 - MODERATE	REACTIVITY 0		
A1 - SLIGHT	SPECIAL 0		
0 - INSIGNIFICANT		LINDON MANUFACTURING 7614 WALLISVILLE ROAD HOUSTON, TEXAS 77020	

SECTION 1 - PRODUCT IDENTIFICATION

TRADE NAME (USED ON LABELS): **6682**
CAS NUMBER: **BLEND**
CHEMICAL DESCRIPTION: **H2S SCAVENGER**
DOT CLASSIFICATION: **FLAMMABLE LIQUID N.O.S.**
HAZARD CLASSIFICATION: **3, UN1993, PG I**
LAST REVISION DATE: **5/13/03**

SECTION II - HAZARDOUS INGREDIENTS

CAS NUMBER	MATERIAL	ACGIH LTV	OSHA PEL
67-56-1	METHANOL	250 PPM	200 PPM
108-01-0	ALKANOLAMINE	NOT DET	20 PPM

SECTION III - PHYSICAL PROPERTIES

SPECIFIC GRAVITY: **0.988 – 1.08**
FLASH POINT: **54 F**
POUR POINT: **ND**
pH: **10.0 – 11.5**
SOLUBILITY IN WATER: **SOLUBLE**
APPEARANCE AND ODOR: **CLEAR TO AMBER LIQUID, MILD ODOR**

CHEMICAL NAME: 6682

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

UEL: N/A

LEL: N/A

EXTINGUISHING MEDIA: DRY CHEMICAL,ALCOHOL FOAM,CARBON DIOXIDE

**COOL CHEMICAL DRUMS EXPOSED TO FIRE WITH WATER SPRAY. FIGHT FIRE FROM A
SAFE DISTANCE. HEAT MAY BUILD UP PRESSURE IN CLOSED CONTAINERS, CAUSING
RUPTURES WHICH INCREASES RISK OF SPREADING FIRE AND/OR CAUSING INJURY. AVOID
STATIC ELECTRICITY.**

SECTION V - REACTIVITY DATA

AVOID: N/A

CHEMICALLY STABLE? Y N

INCOMPATIBLE TO: N/A

**HAZARDOUS DECOMPOSITION (ACUTE AND CHRONIC) BYPRODUCTS: OXIDES OF
CARBON**

SECTION VI - HEALTH HAZARD DATA

**HEALTH HAZARDS (ACUTE & CHRONIC): MAY CAUSE SKIN AND EYE IRRITATION,
BREATHING FUMES MAY CAUSE HEADACHE, DIZZINES. TOXIC IF SWALLOWED.**

CARCINOGENICITY - OSHA REGULATED: N/A

SIGNS & SYMPTOMS OF OVEREXPOSURE

INHALATION: HEADACHE AND OR DIZZINESS.

**SKIN & EYE CONTACT: SKIN IRRITATION DEVELOPS SLOWLY AFTER CONTACT. EYE
IRRITATION DEVELOPS IMMEDIATELY AFTER CONTACT.**

**INGESTION: IF SWALLOWED, MAY CAUSE DROWSINESS, UNCONSCIOUSNESS,
GASTROINTESTINAL PAIN,CRAMPS, NAUSEA,VOMITING AND DIARRHEA.**

EMERGENCY & FIRST AID PROCEDURES

**IN CASE OF EYE CONTACT FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES.
GET IMMEDIATE MEDICAL ATTENTION. FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF INHALED
REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH.
IF BREATHING IS DIFFICULT GIVE OXYGEN. IF SWALLOWED INDUCE VOMITING. GET IMMEDIATE MEDICAL
ATTENTION.**

CHEMICAL NAME: 6682

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

CHRONIC SKIN AND EYE DISORDERS

SECTION VII - SPILL & LEAK PROCEDURES

IF MATERIAL IS SPILLED OR RELEASED

IN CASE OF SPILLAGE, ABSORB WITH INERT MATERIAL AND DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.

HAZARDOUS WASTE: DISPOSE OF ACCORDING TO FEDERAL AND STATE REGULATIONS.

PRECAUTIONS TO BE TAKEN IN STORAGE AND HANDLING

STORE AWAY FROM HEAT AND FLAMES IN A DRY COOL AREA.

OTHER PRECAUTIONS

KEEP AWAY FROM HEAT, SPARKS AND FLAME. USE WITH ADEQUATE VENTILATION AND PROPER RESPIRATORY PROTECTION (FILTER MASKS OR POSITIVE PRESSURE BREATHING MASKS.)

SECTION VIII - CONTROL MEASURES

IF TLV OR PEL IS EXCEEDED WORKERS SHOULD USE ADEQUATE VENTILATION AND PROPER RESPIRATORY PROTECTION (FILTER MASKS OR POSITIVE PRESSURE BREATHING MASKS).

LOCAL EXHAUST SHOULD BE USED IN CLOSED AREAS.

PROTECTIVE GLOVES SUITABLE FOR HYDROCARBON SOLVENTS OR ACIDS SHOULD BE WORN.

CHEMICAL GOGGLES OR FULL FACE SHIELD SHOULD BE WORN AT ALL TIMES.

SECTION IX - SPECIAL PRECAUTIONS

STORE AWAY FROM IGNITION SOURCES. WASH CONTAMINATED CLOTHING BEFORE REUSE.

CHEMICAL NAME: 6682

FEDERAL EPA

COMPREHENSIVE ENVIRONMENTAL RESPONSE , COMPENSATION AND LIABILITY ACT OF 1990 (CERCLA) REQUIRES NOTIFICATION OF THE NATIONAL RESPONSE CENTER OF THE RELEASE OF HAZARDOUS SUBSTANCES EQUAL OR GREATER THAN THE REPORTABLE QUANTITIES (Rq's) IN 40 CFR 302.4

COMPONENTS PRESENT IN THIS PRODUCT AT A LEVEL WHICH COULD REQUIRE REPORTING UNDER THE STATUTE ARE:

**REPORTING
67-56-1 METHANOL RQ = 5000 % IN FORMULA**

THIS MATERIAL AND THE CONTAINER IT IS SHIPPED IN MUST DISPOSED OF IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS AND REQUIREMENTS. NO WARRANTY, EXPRESSED OR IMPLIED OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE IS MADE. BUYER ASSUMES ALL RISK OF USE, STORAGE, AND HANDLING. LINDON MAN. & LAB. L.L.C. SHALL NOT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGE ARISING DIRECTLY OR IT.
